

DEFENDER SELECT

High Performance Nozzles with Multiple Constant Gallonage Flows

DATA MEASUREMENTS AT 100 PSI PRESSURE

- Constant gallonage in all positions and flows.
- 4 Gallonage selection ring, without pattern changes.
- Flush position capable of flushing without pattern changes or shutting down.
- Extruded aluminum, lightweight, hard-coated and durable.
- Durable polymer shut-off handles.
- Designed for use with foam eductors and foam tubes.
- Spinning Teeth in polyethylene, and also in Stainless Steel (under request).



AVAILABLE IN SIZES:



See next page for specifications.

1" DEFENDER SELECT

NOZZLE PART NO. #	Position	GPM	Stream Setting	Effective Reach (ft)	Size	Weight (lbs)	Length (inch)
NZDSC1/15-30-50-60	1	15	SS	62	1"	3.44	7.87
	2	30	SS	85			
	3	50	SS	102			
	4	60	SS	112			

1 1/2" DEFENDER SELECT

NOZZLE PART NO. #	Position	GPM	Stream Setting	Effective Reach (ft)	Size	Weight (lbs)	Length (inch)
NZDSC15/30-60-90-125	1	30	SS	85	1 1/2"	4.3	8.85
	2	60	SS	112			
	3	95	SS	131			
	4	125	SS	141			
NZDSC15/75-100-125-150	1	75	SS	118	1 1/2"	4.3	8.5
	2	100	SS	131			
	3	125	SS	141			
	4	150	SS	148			
NZDSC15/95-125-150-200	1	95	SS	128	1 1/2"	6.57	11.2
	2	125	SS	141			
	3	150	SS	148			
	4	200	SS	154			

2 1/2" DEFENDER SELECT

NOZZLE PART NO. #	Position	GPM	Stream Setting	Effective Reach (ft)	Size	Weight (lbs)	Length (inch)
NZDSC25/95-125-150-200	1	95	SS	128	2 1/2"	7.3	12.8
	2	125	SS	141			
	3	150	SS	148			
	4	200	SS	154			
NZDSC25/125-150-200-250	1	125	SS	141	2 1/2"	7.3	12.8
	2	150	SS	148			
	3	200	SS	151			
	4	250	SS	157			