

# Nozzles

## Constant & Dual Gallonage



**NZ009**  
1" NPSH  
10 to 24 GPM



**NZ015**  
1" NPSH  
20 to 60 GPM



**NZ012**  
1.5" NPSH  
20 to 60 GPM

Red Anodized Coating is standard

- Constructed of light weight Aluminum & Stainless Steel
- Heavy duty bumper for added protection
- Ideal for Fire Fighting and Industrial Applications
- Adjustable from fog to straight stream

- DUAL GALLONAGE** } 10 to 24 GPM - Specify Thread and Size  
20 to 60 GPM - Specify Thread and Size  
20 to 100 GPM - Specify Thread and Size
- CONSTANT GALLONAGE** } 35 GPM - Specify Thread and Size  
100 GPM - Specify Thread and Size



## Forestry



**NZ008**  
1" NPSH  
10 to 25 GPM

Without bumper

Straight Ridge  
Knurled Pattern

Simple quick twist adjusts  
the flow pattern



Additional protection  
with bumper

**NZ011**  
1.5" NH  
20 to 60 GPM

- Constructed of light weight Aluminum & Stainless Steel
- Optional heavy duty bumper for added protection
- Meets or exceeds USDA FS 5100 Series Specifications
- Red Anodizing is standard

## Bail Shutoffs

The Ergonomic Pistol Grip of Bail Shut off attaches to our nozzles providing a tailored system.



**BV11 Bail Shut Off** 1" NH Full Time Swivel x 1" NH M  
**BV115 Bail Shut Off** 1" NH Full Time Swivel x 1 1/2" NH M  
**BV1515 Bail Shut Off** 1 1/2" NH Full Time Swivel x 1 1/2" NH M



**PG11 / PG115**

**PG1515**


**PG11 Pistol Grip with Shut Off**  
1" NH Full Time Swivel x 1 NH M

**PG115 Pistol Grip with Shut Off**  
1" NH Full Time Swivel x 1 1/2" NH M

**PG1515 Pistol Grip with Shut Off**  
1 1/2" NH Full Time Swivel x 1 1/2" NH M



## Specialty Nozzles



**NZ024**  
4 Spray diameters:  
5/16", 1/4", 3/16", 1/8"  
offers you different volumes.  
Just rotate the tip  
to the desired setting.



**NZ027 Adjustable Fan Stream Nozzle**  
Bail Handle creates either a  
Wide Band or Smooth Bore  
reaching distances up to 80 ft.