

PATRIOT SERIES

The Ultimate Concept in Firefighting Nozzles!

DATA MEASUREMENTS AT 100 PSI PRESSURE

- Constant Gallonage in all positions and Flows
- Improved FOG, more uniform, with smaller water drops.
- Ease of maintenance.
- No spinning teeth to break.
- Less friction loss through the nozzle.
- FLUSH position capable of flushing without shutting down.
- Better stream conversion.
- Optional low expansion foam tube available.
- Designed to accomplish with the requirements of NFPA 1964 and EN15182-1, EN15182-2 Type 3.



AVAILABLE IN SIZES:



1½"

See next page for Patriot model specifications.

1 1/2" PATRIOT SERIES

NOZZLE PART NO. #	Position	GPM	Stream Setting	Effective Reach (ft)	Size	Weight (lbs)	Length (inch)
NZIP15/30-60-95-125	1	30	SS	85	1 1/2"	4.2	9.2
	2	60	SS	112			
	3	95	SS	131			
	4	125	SS	141			
NZIP15/30-60-95-125-150	1	30	SS	85	1 1/2"	4.2	9.2
	2	60	SS	112			
	3	95	SS	131			
	4	125	SS	141			
	5	150	SS	148			
NZIP15/75-100-125-150	1	75	SS	118	1 1/2"	4.2	9.2
	2	100	SS	131			
	3	125	SS	141			
	4	150	SS	148			
NZIP15/95-125-150-200	1	95	SS	131	1 1/2"	6.6	10.8
	2	125	SS	141			
	3	150	SS	148			
	4	200	SS	154			